



# Dahua DHI-ASA2212GL-D Fingerprint Time Attendance - Built-in Battery & Wi-Fi



**BDT 5,500.00** ✓ In Stock

### FEATURES :

- > Built of PC and ABS material, and comes with 2.4" LCD with a resolution of 240 (H) × 320 (V).
- > Built-in rechargeable lithium battery, which can be used for about 3 hours after being fully charged.
- > Convenient to configure through its webpage that is accessible to both computers and mobile devices.
- > Attendance can be marked through card(ID), password and fingerprint.
- > Supports 3,000 users, 3,000 cards, 3,000 fingerprints, and 100,000 attendance records.

01711-766062, 01711-461346  
www.timeattendance.com.bd

TIME ATTENDANCE BD



## SPECIFICATIONS :

<b>System</b>	
Main Processor	Embedded Processor
Button Type	Mechanical
Network Protocol	IPv4;UDP;P2P;IPv6;TCP
OSDP Protocol	Yes
Input Method	T9
Interoperability	ONVIF;CGI
SDK	Yes
API	Yes
<b>Basic</b>	
Display Screen	2.4-inch display screen
Product Type	Attendance Standalone
Screen Type	Non-touchscreen
Screen Resolution	240 (H) × 320 (V)
Voice Prompt	Yes
Powering On/Off Button	1
Casing Material	PC + ABS
<b>RFID</b>	
Card Type	ID card
Modulation Type	AM
Frequency Range	125KHz
Max. Transmission Power	66dBuA/m @10m
<b>Function</b>	
Period List	128 periods
Holiday Period	128 periods
Network Update	Yes
Restricted List/Trusted List	Yes
Auto Registration	Yes
<b>Performance</b>	
Response Time	0.2 S
Card Reading Distance	3 cm (1.18")
Fingerprint Sensor Type	Optical
Fingerprint Verification Mode	1:N
Fingerprint Comparison Time	1.5 S
Fingerprint Recognition Time	0.5 S
<b>Attendance</b>	
Export Attendance Record	USB flash drive export
Attendance Check Mode	Auto/Manual Mode;Auto Mode;Manual Mode;Fixed Mode
Attendance Statistics	Yes
Department Setting	20 departments
Schedule Setting	24 shifts
Ring Tone	Yes
<b>User</b>	
User (Card) Type	General user, VIP user, patrol user, guest user, blacklist user, other users, custom user 1 and custom user 2
<b>Capacity</b>	
User Capacity	3,000
Fingerprint Capacity	3000
Card Capacity	3000

<b>Password Capacity</b>	<b>3000</b>
<b>Record Capacity</b>	<b>100000</b>
<b>Port</b>	
<b>USB</b>	<b>1 × USB 2.0 port</b>
<b>Network Port</b>	<b>1 × RJ-45 10/100 Mbps self-adaptive Ethernet port</b>
<b>Exit Button</b>	<b>1 channel</b>
<b>Door Status Detection</b>	<b>1 channel</b>
<b>Lock Control</b>	<b>1 channel</b>
<b>Alarm</b>	
<b>Duress Alarm</b>	<b>Yes</b>
<b>Door Sensor Timeout</b>	<b>Yes</b>
<b>Intrusion</b>	<b>Yes</b>
<b>Illegal Card Exceeding Threshold</b>	<b>Yes</b>
<b>General</b>	
<b>Power Adapter</b>	<b>Included</b>
<b>Power Supply</b>	<b>12 VDC, 1 A; Lithium battery</b>
<b>Power Consumption</b>	<b>≤6 W</b>
<b>Product Dimensions</b>	<b>181.6 mm × 135.6 mm × 32.7 mm (7.15" × 5.34" × 1.29")</b>
<b>Packaging Dimensions</b>	<b>Single device in inner box: 298 mm × 162 mm × 71 mm (11.73" × 6.38" × 2.80") Protective case: 383 mm × 313 mm × 349 mm (15.08" × 12.32" × 13.74")</b>
<b>Operating Temperature</b>	<b>-10 °C to +55 °C (+14 °F to +131 °F)</b>
<b>Operating Humidity</b>	<b>5%-95% (RH), non-condensing</b>
<b>Operating Environment</b>	<b>Indoor</b>
<b>Gross Weight</b>	<b>0.61 kg (1.34 lb)</b>
<b>Installation</b>	<b>Surface Mount</b>
<b>Certifications</b>	<b>CE</b>
<b>Storage Temperature</b>	<b>-20 °C to +70 °C (-4 °F to +158 °F)</b>
<b>Storage Humidity</b>	<b>30%-75% (RH), non-condensing</b>