



BDT 0.00 ✓ In Stock

FEATURES :

- Model: DS-K1201AEF
- Optical CMOS Fingerprint Module
- Max. 5000 fingerprints storage
- Built-in buzzer for status indication
- Supports EM card reading

01711-766062, 01711-461346
www.timeattendance.com.bd

TIME ATTENDANCE BD
—•••••—

Hikvision DS-K1201AEF Specification:

Fingerprint Capacity	Max. 5000 fingerprints storage
Interface	TAMPER: 1
Others	A group of messy code encrypted data for the security of fingerprint storage Supports RS-485 communication with 19200bps-N-8-1 transmission rate. There are CRC test for the protocol Supports EM card reading Card induction distance is 30 mm to 100 mm Supports multiple authentication modes (card, fingerprint, and card + fingerprint) Optical CMOS fingerprint module. The characters of fingerprint can be export to the card reader Adopts the optical fingerprint module, supporting 1:N mode (fingerprint, card + fingerprint) and 1:1 mode (card + fingerprint) Fingerprint comparison time: $1:1 \leq 1 \text{ s}$, $1:1000 \leq 1 \text{ s}$; $\text{FRR} \leq 0.01\%$, $\text{FAR} \leq 0.001\%$ Communication circuit is designed with optical coupling isolation and noise suppression function Built-in buzzer for status indication Accurate data and time display provided by built-in electronic clock and watchdog program to ensure the basic function of the terminal Tamper-proof function
Dimension	62 mm × 132 mm × 44 mm (2.44" × 5.20" × 1.73")
Power Supply	12 VDC ± 10%