



**BDT 85,000.00** ✓ In Stock

## FEATURES :

- Recognition dist.: 0.3 to 3m
- Face capacity: 1,00,000
- Fingerprint: 10,000
- Transaction Logs: 5,00,000
- Display: 7" Touch Screen
- Wi-Fi, TCP/IP, RS-485

01711-766062, 01711-461346  
www.timeattendance.com.bd

TIME ATTENDANCE BD  
—|||—

## Hikvision DS-K1T673TDWX Specification:

|                                 |                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Card Capacity:                  | 5,00,000                                                                                                               |
| Face Capacity:                  | 1,00,000                                                                                                               |
| Event Capacity:                 | 150,000                                                                                                                |
| Face Recognition Accuracy Rate: | ≥ 99%                                                                                                                  |
| Card Type:                      | Mifare 1 card, DESfire card, Felica card                                                                               |
| Card Reading Distance:          | 0 to 3 cm                                                                                                              |
| Card Reading Duration:          | □ 1 s                                                                                                                  |
| Face Recognition Duration:      | □ 0.2 s per person                                                                                                     |
| Face Recognition Distance:      | 3 to 3 m                                                                                                               |
| Power Supply:                   | 12 VDC to 24 VDC/2 A                                                                                                   |
| Working Temperature:            | -30 °C to 60 °C (-22 °F to 140 °F)                                                                                     |
| Working Humidity:               | 0 to 90% (no condensing)                                                                                               |
| Dimensions:                     | 5 mm × 209.2 mm × 24 mm (4.35" × 8.24" × 0.94")                                                                        |
| Language:                       | English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil), Japanese, Korean |
| Weight:                         | Gross Weight□1.06 kg (2.34 lb); Net Weight□0.57 kg (1.26 lb)                                                           |