



BDT 2,800.00 ✓ In Stock

FEATURES :

- Magnetic lock supports up to 272 kg (600 Lbs) of thrust
- Power supply can be 12 VDC or 24 VDC, (default voltage is 12 VDC)
- Suitable for wooden door, glass door, metal door
- High strength material anodized aluminum housing
- Magnetic lock , completely using electromagnetic suction work
- Abrasion-proof materials

01711-766062, 01711-461346
www.timeattendance.com.bd

TIME ATTENDANCE BD

Hikvision DS-K4H255S Specification:

Power supply	12 VDC to 24 VDC, 470 mA to 235 mA
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	0 to 95 % (relative humidity)
Dimensions	Lock Body: 250 mm × 28 mm × 48 mm (9.8" × 1.1" × 1.9") Armature Plate: 180 mm × 38 mm × 12 mm (7.1 × 1.5" × 0.5")
Waight	1.9 kg (4.2 lb)
Material Shell:	hard Anodizing Electroplating Operated Lock Body: eco-friendly Zinc Electroplating Operated Armature Plate: eco-friendly Zinc Electroplating Operated
Door type	Glass door, wooden door, and metal door
Thrust	Max. 272 kg (600 Lbs)