




BDT 0.00 ✓ In Stock

FEATURES :

- Modern Design & Interactive UI
- Revolutionary BioID Fingerprint Sensor
- Multiple Verification Modes: Fingerprint / Card / Password
- Outstanding Performance With Dry, Wet and Rough Fingers

01711-766062, 01711-461346
www.timeattendance.com.bd

TIME ATTENDANCE BD



ZKTeco ProCapture-WP Specification:

CAPACITY	Fingerprint: 20,000, Card: 10,000, Transaction: 100,000
COMMUNICATION	TCP/IP, RS485 (For Slave Reader), Wiegand Input / Output, Security Relay Box
ACCESS CONTROL INTERFACE	Lock Relay Output, Alarm Output / Auxiliary Input/ Exit Button / Door Sensor, Doorbell Output
HARDWARE	1.2GHz High Speed CPU, Memory 128MB RAM / 256MB Flash, BioID Fingerprint Sensor 2.4 Inches TFT-LCD Screen, 125KHz EM Reader / Mifare (Optional), Hi-Fi Voice & Indicator, Anti-dismantle Alarm, Touch Keypad
STANDARD FUNCTIONS Access Levels / Groups / Holidays/ DST / Bell Schedule, Duress Mode, Anti-Passback, Record Query, Custom Wallpaper & Screen Saver	Access Levels / Groups / Holidays/ DST / Bell Schedule, Duress Mode, Anti-Passback, Record Query, Custom Wallpaper & Screen Saver
SPECIAL FUNCTIONS	Multiple Verification Modes, ZK Encrypted Card (Optional), Fingerprint Card (Optional)
COMPATIBILITY	Wiegand Slave Reader, RS485 FP Slave Reader, ZKBioSecurity Software
WORKING TEMPERATURE	-10 °C ~ 50 °C
DIMENSIONS	202.30×96.80×35.00mm
ALGORITHM	Fingerprint Algorithm ZKFinger v10.0
POWER	Operating Voltage 12V DC, Current Draw < 500mA
ADDITIONAL INFO	Package Includes 12V 3A Power Supply