



ZKTeco ProFace X [P] Face & Palm Verification Terminal with Mask Detection



BDT 0.00 ✓ In Stock

FEATURES :

- Fast facial and palm recog
- Anti-spoofing algorithm
- Ultra-large capacity
- IP68 and IK04
- Award-winning access ctrl

01711-766062, 01711-461346
www.timeattendance.com.bd

TIME ATTENDANCE BD



ZKTeco ProFace X [P] Specification:

FACE CAPACITY	30,000 (1:N) / 50,000 (Optional)
PALM CAPACITY	5,000 (1:N)
CARD CAPACITY	50,000
TRANSACTION CAPACITY	1,000,000
USER PHOTO CAPACITY	10,000
EVENT PHOTO CAPACITY	10,000
INSTALLATION	Wall-mount installation version
COMPATIBILITY	Security Relay Box / Wiegand / RS485 / RS232 Slave Reader with FP / RFID / Barcode / QR-code ZKBioSecurity Software
CPU	900MHz Dual Core Customized AI CPU
MEMORY	512MB RAM / 8G Flash
DISPLAY	8" Hight light (400lux) IPS Touch LCD
RESOLUTION	800 x 1280 px
RFID	125KHz EM Reader / 13.56MHz MF(Optional)
CAMERA	2MP WDR Low Light Camera
HARDWARE	Adjustable Light brightness LED / Hi-Fi Voice / Receiver sensitivity Microphone / Distance Detection Sensor / Reset Button and Tamper Switch
ACCESS CONTROL INTERFACE	Lock Relay Output Alarm Output / Auxiliary Input Exit Button/Door Sensor
SPECIAL FUNCTIONS	Wore mask detection / 0.3s High Speed Face Verification / Live Face detection / Communication Https Encrypted Optional / Event Snapshot
STANDARD FUNCTIONS	Access Levels, Groups, Holidays, DST, , Duress Mode (Password), Anti-Passback, Record Query, Custom Wallpaper & Screen Saver, Tamper Switch Alarm
COMMUNICATION	TCP/IP, Wiegand Input / Output, Wi-Fi (Optional), RS485 / RS232

FACE ALGORITHM	ZKLiveFace5.8
PALM ALGORITHM FAR≤0.01%; FRR≤1%	FAR≤0.01%; FRR≤1%
WORKING TEMPERATURE -30℃ ~ 60℃	-30℃ ~ 60℃
WORKING HUMIDITY	≤93%
PROTECTION RATE	IP68 & IK04
DIMENSIONS (H*L*D)	227*143*26mm
POWER Operating Voltage 12V DC	Operating Voltage 12V DC
SUPPORTED SOFTWARE	ZKBioAccess, ZKBioSecurity