



ZKTeco ProFace X [TD] Fast Facial and Temperature & Mask Detection Terminal




BDT 125,000.00 ✓ In Stock

FEATURES :

- Fast facial and palm recog
- Body Temp & Mask Detect
- Anti-spoofing algorithm
- Ultra-large capacity
- IP68 and IK04

01711-766062, 01711-461346
www.timeattendance.com.bd

TIME ATTENDANCE BD



ZKTeco ProFace X [TD] Specification:

Faces	30,000 (1:N) / 50,000 (Optional)Faces 30,000 (1:N) / 50,000 (Optional)
Palm	5,000 (1:N)
Users	50,000
Transactions	1,000,000 / 2,000,000 (Optional)
User Photos	30,000
Event Photos	10,000
Compatibility	Security Relay Box / Wiegand / RS485 / RS232 Slave Reader with FP / RFID / Barcode / QR-code / ZKBioSecurity Software
Hardware	900MHz Dual Core CustomizedComputer vision CPU 512MB RAM / 8G Flash 8" Hight light (400lux) IPS Touch LCD 2MP WDR Low Light Camera Adjustable Light brightness LED Hi-Fi Voice High Sensitivity Microphone Distance Detection Sensor Reset Button and Tamper Switch
Access Control Interface	Lock Relay Output / Alarm Output / Auxiliary Input / Exit Button / Door Sensor
Special Functions	0.3s Hight Speed Facial Verification Liveness Detection HTTPS Communication Encryption (Optional) Event Snapshot
Standard Functions	Access Levels, Groups, Holidays, DST,Duress Mode (Password), Anti-Passback, Record Query, Tamper Switch Alarm,Custom Wallpaper & Screen Saver
Preventative Measures	Mask detection Body temperature detection
Temperature Measurement Distance: 30cm~50cm (1ft~1.64ft) Temperature Measurement Accuracy: $\pm 0.3^{\circ}\text{C}$ ($\pm 32.54^{\circ}\text{F}$)	30cm~50cm (1ft~1.64ft) Temperature Measurement Accuracy: $\pm 0.3^{\circ}\text{C}$ ($\pm 32.54^{\circ}\text{F}$)
Temperature Measurement Range: 34°C~45°C (93.2°F~113°F)	
Temperature Measurement Range:	34°C~45°C (93.2°F~113°F)
Communication	TCP/IP / Wiegand Input / Output / Wi-Fi (Optional) / RS485 / RS232

Face Algorithm:	ZKLiveFace5.8
Palm:	FAR ≤0.01%; FRR ≤1%
Working Temperature:	16°C ~ 32°C (60.8°F ~ 89.6°F)
Working Humidity:	≤93%
Storage Temperature:	-40°C ~ 65°C (-40°F ~ 149°F)
Dimensions (H*L*D):	227*143*26.1mm
Net Weight:	853g