



BDT 0.00 ✓ In Stock

FEATURES :

- Card Capacity: 50,000
- Transactions Capacity: 100,000
- User Photos: 3,000
- Event Photos: 7,000
- Comm: TCP/IP, USB

01711-766062, 01711-461346
www.timeattendance.com.bd

TIME ATTENDANCE BD

ZKTeco ProRF-T Specification:

Card Capacity	50,000
Transactions Capacity	100,000
User Photos	3,000
Event Photos	7,000
Communication	TCP / IP, RS485 (For Slave Reader), USB Host, Wiegand Input / Output, Security Relay Box
Hardware	1.2GHz Dual Core CPU, Memory 128MB RAM / 256MB Flash, 2,4 Inches TFT-LCD Touch Screen, 125KHz EM Reader / Mifare (Optional), Hi-Fi Voice & Indicator, Tamper Switch Alarm, Touch Keypad, 120° Wide Angle Camera
Standard Functions	Access Levels / Groups / Holidays , DST / Bell Schedule, Duress Mode(Password), Anti-Passback, Record Query, Custom Wallpaper & Screen Saver
Special Functions	Multiple Verification Modes, Event Snapshot, User Photo(Optional)
Access Control Interface	Lock Relay Output, Alarm Output / Auxiliary Input, Exit Button / Door Sensor, Doorbell Output
Compatibility	Wiegand Slave Reader, ZKBioSecurity Software, RS485 Card Slave Reader (Optional)
Working Temperature	-10 °C ~ 50 °C
Dimensions	195.5 × 87 × 35 mm.
Power	Operating Voltage 12V DC, Current Draw < 500 mA