



## ZKTeco SFace900 Semi-Outdoor Multi-Biometric Time Attendance & Access Control Terminal



**BDT 29,000.00** ✓ In Stock

### FEATURES :

- Face Capacity: 3,000
- Fingerprint Capacity: 4,000
- Card Capacity: 10,000
- Log Capacity: 100,000
- Battery Backup

01711-766062, 01711-461346  
www.timeattendance.com.bd

TIME ATTENDANCE BD



### ZKTeco SFace900 Specification:

|                       |                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------|
| Display               | 4.3-Inch Touch Screen                                                                                                |
| Face capacity         | 3,000                                                                                                                |
| Fingerprint capacity  | 4,000                                                                                                                |
| ID Card capacity      | 10,000                                                                                                               |
| Logs capacity         | 100,000                                                                                                              |
| Communication         | TCP/IP, RS232/485, USB Host                                                                                          |
| Standard Functions    | Automatic Status Switch, Self-Service Query, Work Code, SMS DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID |
| Interfaces for        | 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm                                                             |
| Optional Functions    | ID/MiFare Card, Wi-Fi, 3G, ADMS, 2000 mAH Backup Battery                                                             |
| Power Supply          | 12V 3A                                                                                                               |
| Operating Temperature | 0 °C- 45 °C                                                                                                          |
| Operating Humidity    | 20%-80%                                                                                                              |
| Dimensions            | 195.5*166.5*120mm (Length*Width*Thickness)                                                                           |
| Package Weight        | 1.6 kg                                                                                                               |