Zkteco TS-2122 Semi-automatic Tripod Turnstiles



BDT 0.00 ✓ In Stock

FEATURES :

- Semi-Automatic
- Anti-tailgate
- Flexible reader installation plate
- Special designed case shape
- Special width 19cm
- SUS304 stainless steel (optional SUS316)

Specification

Power requirements	AC 100 ~ 120V/200 ~ 240V, 50/60Hz
Power consumption	Starting - 73W , Standby - 20W , Unlock - 63W
Working temperature	-28 °C – 60 °C
Working humidity	5%-80%
Working environment	Indoor/Outdoor(if sheltered)
Speed of throughput	RFID -- Maximum 30/minute , Fingerprint -- Maximum 25/minute
Lane width(mm)	520
Footprint(mm*mm)	1120*700
Dimension(mm)	L=1120, W=180, H=985
Dimension with packing(mm)	L=1200, W=280, H=1080
Net weight(kg)	45
Weight with packing(kg)	53
LED indicator	Y
Cabinet material	SUS304 Stainless Steel
Lid material	SUS304 Stainless Steel
Barrier material	SUS304 Stainless Steel
Barrier movement	Rotating
Emergency mode	Y
Security level	Medium
MCBF	1 million
Options/Accessories	Counter, Card Receiver Box, SUS316 Cabinet and Lid, Remote Control