ZKTeco TS2033 Tripod Turnstile Access Control System



BDT 0.00 ✓ In Stock

FEATURES :

- SUS304 stainless steel housing
- Bi-directional tripod turnstile with arm drop function
- LED pictograms for intuitive user experience and high throughput in both directions
- High quality at an affordable price
- Low power consumption

Specification

Power requirements	AC 100 ~ 120V/200 ~ 240V, 50/60Hz
Power requirements Starting	73W
Power consumption Standby	20W
Power consumption Unlock	63W
Working temperature	-28 °C – 60 °C
Working humidity	5%-80%
Working environment	Indoor/Outdoor (if sheltered)
Speed of throughput RFID	Maximum 30/minute
Speed of throughput Fingerprint	Maximum 25/minute
Lane width(mm)	505
Footprint(mm*mm)	785*1110
Dimension(mm)	L=1110, W=280, H=987
Dimension with packing(mm)	L=1175, W=370, H=1070
Net weight(kg)	42
Weight with packing(kg)	48
LED indicator	Y
Cabinet material	SUS304 Stainless Steel
Lid material	SUS304 Stainless Steel
Barrier material	SUS304 Stainless Steel
Barrier movement	Rotating
Emergency mode	Y
Security level	Medium

MCBF	1 million
Options/Accessories	Counter, SUS316 Cabinet and Lid, Remote Control